CENTRIFUGE R-5D



MAXIMUM CAPACITY

12 X 15 ml

MAXIMUM SPEED

5.250 rpm

IDEAL FOR:

SCHOOLS AND LABORATORIES
PRODUCTION DEPARTMENTS
CONTROL LABORATORIES
ROUTINE TEST AND ANALYSIS



R-5D Centrifuge

FEATURES

- **Supplied complete with**:
  - R-83A 12 x15 ml fixed-angle roto ;
  - 12 metal buckets;
  - 15 ml plastic tubes.
- Bright **digital display**
- **Load unbalance control** with acoustic and luminous warning
- **Easiy-access stainless steel** centrifuge chamber
- **Intuitive,** easy-to-read interface
- Automatic **lid locking**
- Brushless, silent and maintenance-free **induction motor**
  (ensures a healthy and safe working environment as it is free of carbon deposits)
- Extremely compact construction with **quality materials** for a long service life
- **Small dimensions** to optimise space on laboratory benches

DATA SHEET

Capacity	12 x 15 ml
Maximum speed	5.250 rpm
Maximum RCF	4.280 x g
Timer	1 to 99 min or continuos
Type of braking	Fast or slow
Transmission system	Direct
Motor type	Brushless induction
Noise level	53 dB
Power supply voltage	220 V ±10% – 50 Hz -250 W
Standard directives	2014/35/EU 2014/30/EU 2015/863 2006/42/EC IEC 61010-1:2010+A1:2016 IEC 61010-2-020:2016 IEC 61326-1:2012 IEC 61010-2-120:2016
Dimensions (H x W x D)	290 x 320 x 440 mm
Weight	18,5 Kg
R-5D Centrifuge Complete with R-83A rotor 12x15 ml fixed angle and 12 metal buckets with 15 ml plastic tubes	**40000062**



R-83 A Rotor



ROTOR AND TUBES SPARES

part number	
40000272	R-83A rotor + test tubes and metal bucket
40000402	Metal bucket + Falcon 15 ml test tube
40000422	Metal bucket + 15 ml plastic test tube
40000682	Adapter for 5/7 ml test tubes with spherical bottom (Ø x L) 13x75 and 13x100 mm

EU Designed Made in India

Distributed by

GIORGIO·BORMAC s.r.l.

CE

ISO certified manufacturer

WARRANTY 2 YEARS

FSC www.fsc.org MISTO Carta | A sostegno della gestione forestale responsabile FSC® C102765