Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

CB 5-20

Code: *41202212*



TECHNICAL DATA SHEET

Standards applied

Regulations	2006/95/EC - 2004/108/EC - EN61326-1:2006 - EN61010-1:2010 - EN61010-2-010:2003
Warranty [years]	2 anni

Supplied as standard

Performance

Temperature Range	-20...+100 °C
Capacity	5
Minimum overall height with lid fully closed	150 mm
Temperature Resolution	0.1 °C
Temperature flutuation at 20°C	±0,2
Volume	5 L
Display	LCD
Timer	99 : 59 hh:mm
Security Class (DIN 12880)	2
Circulation Type	Forced circulation
Pump	Yes
Maximum Pump Flow Rate [l/min]	6.5 l/min
Maximum Pump Pressure [bar]	0.35
Power	2600 W
Inner Tank Depth	150 mm
Overtemperature Safety System	Electronic
Refrigerant Quantity	130 g
Refrigerant	R290
External Circulation	Yes
Refrigeration Capacity at 20°C	410 W
Refrigeration Capacity at 10°C	370 W

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Refrigeration Capacity at 0°C	330 W
Refrigeration Capacity at -10°C	280 W
Refrigeration Capacity at -20°C	160 W

Feeds

Frequency	50 Hz
Power Supply	230 V

Dimensions and weight

Weight	54 kg
External dimension (WxDxH)	380 x 670 x 840 mm
Packaging dimension (WxDxH)	810 x 490 x 1060
Internal Tank dimension (WxDxH)	145 x 150 x 150 mm