Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Refrigerated incubator IC 150 R

Code: *41201512*



TECHNICAL DATA SHEET

Standards applied

Warranty [years]	2 anni
Regulations	2006/95/EC -2004/108/EC - EN61326-1:2006 - EN61010-1:2010 - EN61010-2-010:2003

Performance

Capacity	150 L
Temperature Flutuation at 25°C	±0,1 °C
Temperature variation in space at 25°C	±0,5 °C
Heating up time at 25°C	40 m
working temperature	0...60 °C

Features

Maximum shelf load	10 kg
Security class (DIN 12880)	3.1
Overtemperature safety system	Electronic and electromechanical
Number of shelves	3
Maximum number of shelves	9
Programs	8 programs with up to 8 steps each, 1 single-step program, and 1 multi-step program with up to 64 steps
Internal Data Logger	Yes
Data Export	Yes, via USB stick
Maximum internal recording capacity	200000
Display	Touchscreen
Graph display	Yes
Operation History	Yes
Alarm History	Yes
Ramp function	Yes
Multi-User Function	Yes

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Timer	99 : 59 hh:mm
Heating type	Forced ventilation
Ventilation	3 speeds (50 %, 75 %, 100 %)
Useful volume	150 L
Refrigerant	R1234ZE
Refrigerant Quantity	280 g

Feeds

Power supply	230 V
Frequency	50 - 60 Hz
Absorbed power	1100 W

Dimensions and weight

Dimensions (WxDxH)	650 x 620 x 1350 mm
Internal dimensions (WxDxH)	500 x 360 x 800 mm
Minimum distance between shelves	50 mm
Weight	100 kg