

XS PC 50 VioLab benchtop multiparameter - Cell 2301 T - Without electrode

Code: 50103912



TECHNICAL DATA SHEET

Supplied as standard

Electrode holder stand, coloured buffer solutions, multi-socket power supply
and operating instructions.

Performance

Parameters	pH, mV, ORP, Conducibilità, TDS, Temperatura
pH measuring range	0 ... 14
Accuracy (pH)	±0,02
pH resolution	0,01
Recognised pH buffers	USA - NIST - 2 custom values
PH calibration points	1...3 automatic values - 2 user values
Criteria for stability of the measure	Low - Med - High (pH)
EC measuring range	0,00 µS ... 200 mS
EC accuracy	±2 % f.s.
EC Resolution	0,01 / 0,1 / 1 µS/cm (scala automatica) µS/cm
EC recognised buffers	84 µS - 147 µS - 1413 µS - 12,88 mS - 111,8 mS - 1 valore user
EC calibration points	1...4
Display	0,1 / 1 / 10
Coefficiente di temperatura	0,00 ... 10,00
Reference temperature	+15 ... +30
Temperature compensation	0,00...80,0 °C
TDS measuring range	0,1 mg/l ... 200 g/l
TDS factor	0.40 ... 1.00
mV / ORP measuring range	-1000 ... +1000
ORP resolution	1
ORP calibration points	1
temperature measurement range	0,0 ... +100,0
Temperature accuracy	±0,5 °C

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Temperature resolution	0,1 °C
------------------------	--------

Features

Display	High-definition, backlit colour LCD
DHS compatibility	Yes
Languages	BNC - RCA
Working temperature	0 ... +45
IP rating	54

Feeds

Dimensions and weight

Dimensions (WxDxH)	180*145*55 mm
Weight	0.38

Standards applied

Regulations	CE
-------------	----