Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Centrifuge NEYA 10 PROFESSIONAL ventilated 4x175 ml, 6000 rpm, 10 Programmes



Code: *40100312*

TECHNICAL DATA SHEET

Standards applied

Warranty	2 years

Performance

Capacity max. (fixed angle rotor)	6x100 ml
Capacity max. (swing rotor)	4x175 ml
Acceleration ramps	0 ÷ 9 (0 = min. - 9 = max.)
Deceleration ramps	0 ÷ 9 (0 = no brake,1 = min. - 9 = max.)
RCF max (fixed angle rotor)	4800 xg
RCF max (swing rotor)	3600 xg
Noise	55 dB
Maximum speed with fixed angle rotor	6000
Maximum speed with swing rotor	4500 rpm

Features

Imbalance control	Yes
Time and date	Yes
RCF display	Yes
Spin function	Yes
RCF setting	Yes, from 50xg to 4800xg with steps of 50xg
Rotor indication	Yes
Speed limiter	Yes
Programs	10 programs with protection function
Control system	microprocessor and backlit display
Timer	00:30 ÷ 99:50 (mm:ss) and continuously hh:mm
Type of motor	Brushless induction

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Max speed check	Yes

Feeds

Power supply	220
Consumption	500 W
Max. amperes	1.6 A

Dimensions and weight

Entrance height	275 mm
Dimensions (WxDxH)	450 x 590 x 330
Dimensions height when open	670 mm
Weight	40 kg
Weight (with packaging, no rotor)	63 kg