Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

ICF 55 SUPER forced-ventilation incubator

Code: *41200902*



TECHNICAL DATA SHEET

Standards applied

Warranty [years]	2 anni
Regulations	2006/95/EC -2004/108/EC - EN61326-1:2006 - EN61010-1:2010 - EN61010-2-010:2003

Performance

Capacity	57 L
working temperature	+5 Ta...80 °C
Temperature fluctuation at 37°C	±0,1 °C
Temperature variation in space at 37°C	±0,3 °C
Heating time at 37°C	30 m

Features

Maximum shelf load	20 kg
Security class (DIN 12880)	3.1
Overtemperature safety system	Electronic and electromechanical
Number of shelves	2
Maximum number of shelves	5
Programs	8 programs with up to 8 steps each, 1 single-step program, and 1 multi-step program with up to 64 steps
Internal Data Logger	Yes
Data Export	YES, via USB stick
Maximum internal recording capacity	200000
Display	Touch screen
Graph display	Yes
Operation History	Yes
Alarm History	Yes
Ramp function	Yes
Multi-User Function	Yes

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Door Switch	Yes
Door Alarm	Yes, 5 minutes delay
Timer	99 : 59 hh:mm
Heating type	Forced ventilation
Ventilation	3 speeds (50 %, 75 %, 100 %)
Useful volume	57 L

Feeds

Power supply	230 V
Frequency	50 - 60 Hz
Absorbed power	350 W

Dimensions and weight

Dimensions (WxDxH)	690 x 620 x 650 mm
Internal dimensions (WxDxH)	400 x 350 x 415 mm
Minimum distance between shelves	50 mm
Weight	56 kg