Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

XS pH 8 PRO Basic - benchtop pH meter - Polymer S7 electrode



Code: *50101202*

TECHNICAL DATA SHEET

Performance

pH measuring range	-2,000 ... +16,000 pH
Accuracy (pH)	±0,002 pH
pH resolution	0,1 / 0,01 / 0,001 pH
Recognised pH buffers	USA - NIST - DIN 19266
PH calibration points	1 ... 5 automatic values - 2 user values
Temperature compensation	0,0 ... +100,0 °C
Criteria for stability of the measure	Med - High - Tit
pH alarm range	Min - Max
pH electrode status indication	Yes with graph
Measuring range mV	-2000 ... +2000 mV
mV resolution	
mV / ORP measuring range	-2000 ... +2000 mV
ORP calibration points	1 automatic value - 1 user value
temperature measurement range	-20,0 ... +120,0 °C
Temperature accuracy	±0,2 °C
Temperature Resolution	0,1 °C

Features

Display	4.3" high-definition, backlit colour TFT
Inputs	BNC - RCA
PC Communication	USB type B
Display	Yes with icon
Calibration data indication	Yes with reports
PC connection	USB type B
Printer connection	RS 232
AQA	Yes
Selectable languages	Eng - Ita - Deu - Esp - Fra - Por

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Memory	1000
Datalogger	Manual - Automatic
Password	Yes, 8 numeric characters
Languages	Eng - Ita - Deu - Esp - Fra - Por
Analog view	Yes
Display	Si
Working temperature	0 ... +45 °C
IP rating	54 IP

Feeds

Dimensions and weight

Dimensions (WxDxH) mm	200*165*58
Weight	0,709 kg

Regulations