Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

XS Tester PC 6 - KIT

Code: *50014293*



TECHNICAL DATA SHEET

Performance

Parameters	pH - mV - ORP - Cond - TDS - SAL - T
pH measuring range	-2,00 ... 16,00
Accuracy (pH)	±0,01
pH resolution	0.01
Recognised pH buffers	5 US pads
PH calibration points	1 ... 3
EC measuring range	0,01 µS ... 199,9 mS
EC accuracy	±2 % f. s.
EC Resolution	Scala automatica µs/cm
EC recognised buffers	84 µS / 1413 µS / 12,88 mS
EC calibration points	1 ... 3
Coefficiente di temperatura	0.00 ... 4.00
Reference temperature	20,0 ... 25,0
Temperature compensation	Yes
TDS measuring range	0,01 ppm ... 199,9 ppt
TDS accuracy	±2 % f. s.
TDS factor	0.40 ... 1.00
Salinity measuring range	0,01 mg/l ... 100,0 g/l
mV measuring range	-1000 ... +1000
mV / ORP measuring range	-1000 ... +1000
ORP resolution	0.1 / 1 (automatic scale)
ORP calibration points	1 user-defined
temperature measurement range	0,0 ... +60,0
Temperature accuracy	±0,5
Temperature resolution	0.1 °C

Features

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Display	3-colour backlit LCD
Automatic OFF	After 8 minutes
IP rating	67

Feeds

Dimensions and weight

Dimensions (WxDxH)	40 x 200 mm
Weight	0.11

Standards applied

Regulations	CE