Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

ICF 120 PLUS forced ventilation incubator

Code: *41200812*



TECHNICAL DATA SHEET

Standards applied

Warranty [years]	2 anni
Regulations	2006/95/EC -2004/108/EC - EN61326-1:2006 - EN61010-1:2010 - EN61010-2-010:2003

Performance

Capacity	120 L
working temperature	+5 Ta...80 °C
Temperature fluctuation at 37°C	±0,1 °C
Temperature variation in space at 37°C	±0,4 °C
Heating time at 37°C	40 m

Features

Maximum shelf load	20 kg
Security class (DIN 12880)	3.1
Overtemperature safety system	Electronic and electromechanical
Number of shelves	3
Maximum number of shelves	7
Programs	8 programs with up to 8 steps each, 1 single-step program, and 1 multi-step program with up to 64 steps
Internal Data Logger	Yes
Data Export	Yes, via USB stick
Maximum internal recording capacity	2167
Display	LCD
Graph display	No
Operation History	No
Alarm History	No
Ramp function	No
Multi-User Function	No

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Door Switch	Yes
Timer	99 : 59 hh:mm
Heating type	Forced ventilation
Ventilation	3 speeds (50 %, 75 %, 100 %)
Useful volume	120 L

Feeds

Power supply	230 V
Frequency	50 - 60 Hz
Absorbed power	600 W

Dimensions and weight

Dimensions (WxDxH)	810 x 760 x 750 mm
Internal dimensions (WxDxH)	520 x 435 x 530 mm
Minimum distance between shelves	50 mm
Weight	74 kg