Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Centrifuge NEYA 8 BASIC ventilated, 4x175 ml, 6000 rpm

Code: *40100302*



TECHNICAL DATA SHEET

Standards applied

Warranty	2 years

Performance

Capacity max. (fixed angle rotor)	6 x 100 ml
Capacity max. (swing rotor)	4 x 175 ml
Acceleration ramps	L - M - H (Low - Medium - High)
Deceleration ramps	L - M - H (Low - Medium - High)
RCF max (fixed angle rotor)	4800 xg
RCF max (swing rotor)	3600 xg
Noise	55 dB
Maximum speed with fixed angle rotor	6000
Maximum speed with swing rotor	4500 rpm

Features

Imbalance control	Yes
Time and date	Yes
RCF display	No
Spin function	No
RCF setting	No
Rotor indication	Yes
Speed limiter	Yes
Programs	No
Control system	Microprocessor and multi-colour display
Timer	00:30 ÷ 99:50 (mm:ss) e in continuo hh:mm
Type of motor	Brushless induction
Max speed check	Yes

Feeds

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Power supply	220 ± 10% - 50 Hz
Consumption	500 W
Max. amperes	1.6 A

Dimensions and weight

Entrance height	275 mm
Dimensions (WxDxH)	450 x 590 x 330
Dimensions height when open	670 mm
Weight	40 kg
Weight (with packaging, no rotor)	63 kg